

Applications

CCTV and Video

Operating Temperature

-25 to +75 °C

Max. Operating Voltage

300 Vrms

Sector - BT-Security-TEC™

Coaxial Cables

Standard References

IEC 61196

(BS) EN 50117

(BS) EN 50290-2

RoHS directives

Design

1. Conductor

Flexible Bare or
Tinned Copper

2. Dielectric

Foamed Polyethylene

3. Braid

Bare Copper

4. Sheath Material

Polyvinyl Chloride (PVC)

Standard Put Up Length

305 or 500 metres

Physical Characteristics

Coax Cables for CCTV and Video		RG-59 Flexible Conductor	RG-6 Flexible Conductor	RG-11 Flexible Conductor
BTCL Part Numbers		C1275	C1276	C1277
Conductor Material		Tinned Copper	Bare Copper	Bare Copper
Conductor stranding	mm	19 x 0.18	19 x 0.22	19 x 0.34
Nom. Diameter Dielectric	mm	3.71	4.60	7.11
Nom. Overall Diameter	mm	6.0	6.8	10.0
Coverage Braid	%	95	95	90
Max. Recommended Pulling Tension	N	220	310	640
Min. Bend Radius (Install)	mm	60	68	100
Nom. Cable Weight	kg/km	47.12	54.66	110.0

Electrical Characteristics (at 20°C)

Coax Cables for CCTV and Video		RG-59 Flexible Conductor	RG-6 Flexible Conductor	RG-11 Flexible Conductor
BTCL Part Numbers		C1275	C1276	C1277
Impedance	Ohm	75 ± 3	75 ± 3	75 ± 3
Max. DC Resistance Conductor	Ω/km	40	30	8.8
Max. DC Resistance Screen	Ω/km	10.1	10.8	6.2
Nominal Capacitance	pF/m	53.5	53.5	52.8
Nominal Inductance	μH/m	0.32	0.32	0.32
Velocity of Propagation	%	83	83	84
Nominal Time Delay	ns/m	3.97	3.97	3.97
Min. Return Loss 1 to 1000 MHz	dB	20	20	20

Nominal Attenuation in dB/100m

MHz	5	10	50	100	200	300	400	450	550	700	750	870	1000
RG-59	1.9	2.95	6.23	8.53	11.81	15.3	16.41	18.92	21.03	22.97	24.8	26.84	27.89
RG-6	1.78	2.36	4.92	6.56	9.51	12.43	13.78	15.14	17.15	18.37	19.73	20.26	21.96
RG-11	0.99	1.15	2.96	4.27	6.23	8.27	9.51	10.31	11.51	13.45	13.95	14.87	17.06