

Applications

Multi-Conductor cables suitable for Audio, Control, Instrumentation and Building Management Systems (BMS)

Sector – BT BMS-TEC™

Audio, Control & Instrumentation

Standard References

(BS) EN 50290-2
IEC 60754-1 & 2
IEC 61034
IEC 60332-3C
RoHS directives

Design

1. Conductor

N x Bare Copper wire,
14AWG flexible

2. Insulation

Polyolefin
Core 1: Black
Core 2: White
Core 3: Red
Core 4: Green
Core 5: Brown
Core 6: Blue
Core 7: Orange
Core 8: Yellow

3. Ripcord

4. Sheath Material

Flame-Retardant
Halogen Free (HFFR)
Standard colour: purple

Standard Put Up Length

305 metres

Physical Characteristics

BTCL Part Number	Unit	C1702	C1704	C1706	C1708	C1710
No of cores x 14AWG (19 x 27)		2	3	4	6	8
Nom. Diameter Conductor	mm	1.8	1.8	1.8	1.8	1.8
Nom. Radial Thickness Insulation	mm	0.3	0.3	0.3	0.3	0.3
Nom. Radial Thickness Sheath	mm	0.8	0.8	0.8	0.8	0.8
Nom. Overall Diameter	mm	6.4	6.8	7.4	8.8	9.5

Electrical Characteristics

BTCL Part Number	Unit	C1702	C1704	C1706	C1708	C1710
No of cores x 14AWG (19 x 27)		2	3	4	6	8
Max. DC Resistance Conductor	Ω/km	9.36	9.36	9.36	9.36	9.36
Capacitance conductor to conductor	pF/m	80	75	70	70	70
Nominal Inductance	μH/m	0.5	0.5	0.5	0.5	0.5
Max. Recommended Current at 25°C	Amps	8	8	6.4	5.6	5.6
Max. Operating Voltage	Vrms	300	300	300	300	300

Miscellaneous

BTCL Part Number	Unit	C1702	C1704	C1706	C1708	C1710
No of cores x 14AWG (19 x 27)		2	3	4	6	8
Operating Temperature	°C	-25 / +75	-25 / +75	-25 / +75	-25 / +75	-25 / +75
Max. Recommended Pulling Tension	N	420	635	845	1265	1685
Min. Bend Radius (install)	mm	64	68	74	89	95
Nominal Cable Weight	kg/km	62.6	84.1	105.8	150.3	191.9