

Applications

Multi-Conductor cables suitable for Audio, Control, Instrumentation and Building Management Systems (BMS)

Sector – BT BMS-TEC™

Audio, Control & Instrumentation

Standard References

(BS) EN 50290-2
IEC 60754-1 & 2
IEC 61034
IEC 60332-3C
RoHS directives

Design

1. Conductor

N x Bare Copper wire,
18AWG flexible

2. Insulation

Polyolefin
Core 1: Black
Core 2: Red
Core 3: White
Core 4: Green
Core 5: Brown
Core 6: Blue
Core 7: Orange
Core 8: Yellow

3. Ripcord

4. Sheath Material

Flame-Retardant
Halogen Free (HFFR)
Standard colour: purple

Standard Put Up Length

305 metres

Physical Characteristics

BTCL Part Number	Unit	C1722	C1724	C1726	C1728	C1730
No of cores x 18AWG (7 x 26)		2	3	4	6	8
Nom. Diameter Conductor	mm	1.2	1.2	1.2	1.2	1.2
Nom. Radial Thickness Insulation	mm	0.25	0.25	0.25	0.25	0.25
Nom. Radial Thickness Sheath	mm	0.8	0.8	0.8	0.8	0.8
Nom. Overall Diameter	mm	5.0	5.3	5.7	6.7	7.2

Electrical Characteristics

BTCL Part Number	Unit	C1722	C1724	C1726	C1728	C1730
No of cores x 18AWG (7 x 26)		2	3	4	6	8
Max. DC Resistance Conductor	Ω/km	22.7	22.7	22.7	22.7	22.7
Capacitance conductor to conductor	pF/m	70	65	65	60	60
Nominal Inductance	μH/m	0.5	0.5	0.5	0.5	0.5
Max. Recommended Current at 25°C	Amps	5	5	4	3.5	3.5
Max. Operating Voltage	Vrms	300	300	300	300	300

Miscellaneous

BTCL Part Number	Unit	C1722	C1724	C1726	C1728	C1730
No of cores x 18AWG (7 x 26)		2	3	4	6	8
Operating Temperature	°C	-25 / +75	-25 / +75	-25 / +75	-25 / +75	-25 / +75
Max. Recommended Pulling Tension	N	200	299	399	600	797
Min. Bend Radius (install)	mm	50	53	57	67	72
Nominal Cable Weight	kg/km	34.7	45.5	56	78.4	99