

### Application

The cable is designed primarily for track-side railway installation. It is a petroleum jelly filled, twisted pair cable suitable for duct installation with a bonded moisture barrier sheath, and for buried or open channel installation, with an additional protection of a bonded corrugated steel tape and sheath. The additional protection provides protection against rodent attack. The product satisfies the requirements of Network Rail Specification NR/PS/TEL/00015 (formerly GK/RT 0315) and Specifications TS0886 and BR1822.

### Construction

Twisted pairs in 10 Pair Units. The pair range is 2 – 100.

Number Pairs	Nominal Cdr Size (mm)	Minimum Elongation (%)	Nominal Ins. Diameter (mm)	Duct / Inner Sheath Cable		Armoured Cable		Min Bend Radius (mm)	Cable Weight (kg/km)
				Min. Radial (mm)	Diameter Max. (mm)	Min. Radial (mm)	Diameter Max. (mm)		



### Product Description

Plain annealed solid copper wire, solid polyethylene insulation, twisted pairs, petroleum jelly filling, water swellable tape, paper core wrap, black polyethylene sheath incorporating a longitudinally applied aluminium/polyethylene moisture barrier, and corrugated steel tape armour bonded to a black polyethylene sheath

2	0.63	15	1.15	1.6	10.5	1.60	18.0	360	222
5	0.63	15	1.15	1.6	12.0	1.60	19.5	390	296
10	0.63	15	1.15	1.6	13.8	1.60	20.3	406	383
20	0.63	15	1.15	1.6	16.3	1.60	23.8	476	504
30	0.63	15	1.15	1.6	18.6	1.60	26.1	522	606
50	0.63	15	1.15	1.6	22.4	1.60	29.9	598	903
75	0.63	15	1.15	1.6	26.4	1.60	33.9	678	1202
100	0.63	15	1.15	1.6	29.2	1.60	36.7	734	1463

2	0.90	15	1.50	1.6	11.5	1.60	19.0	380	250
5	0.90	15	1.50	1.6	13.8	1.60	21.3	426	370
10	0.90	15	1.50	1.6	16.3	1.60	23.8	476	508
20	0.90	15	1.50	1.6	20.1	1.60	27.6	552	782
30	0.90	15	1.50	1.6	23.4	1.60	30.9	618	1000
50	0.90	15	1.50	1.6	28.2	1.60	35.7	714	1402
75	0.90	15	1.50	1.6	34.0	1.60	41.5	830	2055
100	0.90	15	1.50	1.6	37.3	1.60	44.8	896	2550

### Electrical Properties

Cable Size	Cu Size (mm)	Mutual Capacitance (nF/km)		Conductor Resistance @ 20°C (ohms)	
		Max Average	99%	Max Average	99%
20 Pairs or less	0.63	70.0	79	58.0	60.0
	0.90	79.0	85	28.0	30.0
More than 20 Pairs	0.63	67.0	75.0	58.0	60.0
	0.90	75.0	81.0	28.0	30.0

PACW/ solid polyethylene insulation/moisture barrier/PJ filled/polyethylene sheathed  
External Telephone Cable  
(Complies with Specifications NR/PS/TEL/00015 and TS0886/T1822)

Attenuation & Near-End Crosstalk	Cu Size (mm)	Measurement Frequency			
		1.0 kHz	2.4 kHz	1.024 MHz	
Attenuation dB/km (Max Ave)	0.63	1.40	2.15	18.70	
	0.90	0.95	1.46	14.60	
NEXTA (dB Minimum)		70.00	65.00	Within Unit	Between Units
				40.00	47.00

### Insulation Resistance

Insulation resistance measurements shall be made with not less than 500 volts D.C. After steady electrification for one minute the insulation resistance measured between each conductor and the remaining conductors connected together shall be not less than 1500 megohms per 1000 metres at 20°C.

### Capacitance Unbalance

Not more than 1% of the corrected capacitance unbalance measurements between adjacent pairs shall exceed the following values:

Two-Pair (Quad) Cable 800pF. All other sizes 275pF.

### Pair Colour Scheme, Unit Binder Colours and Cable Make-up

Cabling Element No.	a-wire	b-wire	Unit Number	Binder Colour	Cable Size	No. and Pair Size of Unit in Centre and 1 <sup>st</sup> Layer		
						Centre	1 <sup>st</sup> layer	
1	WHITE	BLUE	1	BLUE	2	1 x 2	-	
2	WHITE	ORANGE	2	ORANGE	5	1 x 5	-	
3	WHITE	GREEN	3	GREEN	10	1 x 10	-	
4	WHITE	BROWN	4	BROWN	20	4 x 5	-	
5	WHITE	GREY	5	GREY		2 x 10	-	
6	RED	BLUE	6	WHITE	30	6 x 5	-	
7	RED	ORANGE	7	RED		3 x 10	-	
8	RED	GREEN	8	BLACK	50	5 x 10	-	
9	RED	BROWN	9	YELLOW		1 x 10	4 x 10	
10	RED	GREY	10	VIOLET	75	3 x 5	6 x 10	
						100	2 x 10	8 x 10
							3 x 10	7 x 10
						4 x 5	8 x 10	